

Constant Tension Clamps

Breeze T-Bolt Spring-Loaded


Breeze Spring-Loaded T-Bolt clamps provide comprehensive application coverage and are performance engineered. They meet the same durability, torque and quality standards as the standard Breeze T-Bolt clamps. The spring design adds constant tension performance. Available in standard and heavy duty springs.

3/4" (19mm) band


Per SAE standard J1508 Type "SLTB"



T-BOLT SPRING DIMENSIONS					
Min.		Max.		Standard Duty Part Number B9226	Heavy Duty Part Number B9224
in.	mm	in.	mm		
2.13	54	2.44	61.9	-0213	-0213
2.25	57.2	2.56	65.1	-0225	-0225
2.38	60.3	2.69	68.3	-0238	-0238
2.5	63.5	2.81	71.4	-0250	-0250
2.63	66.7	2.94	74.6	-0263	-0263
2.75	69.9	3.06	77.8	-0275	-0275
2.88	73	3.19	81	-0288	-0288
3	76.2	3.31	84.1	-0300	-0300
3.06	77.8	3.38	85.7	-0306	-0306
3.13	79.4	3.44	87.3	-0313	-0313
3.25	82.6	3.56	90.5	-0325	-0325
3.38	85.7	3.69	93.7	-0338	-0338
3.5	88.9	3.81	96.8	-0350	-0350
3.56	90.5	3.88	98.4	-0356	-0356
3.63	92.1	3.94	100	-0363	-0363
3.75	95.3	4.06	103.2	-0375	-0375
4.06	103.2	4.38	111.1	-0406	-0406
4.13	104.8	4.44	112.7	-0413	-0413
4.25	108	4.56	115.9	-0425	-0425
4.5	114.3	4.81	122.2	-0450	-0450
4.56	115.9	4.88	123.8	-0456	-0456
5	127	5.31	134.9	-0500	-0500
5.25	133.4	5.56	141.3	-0525	-0525
5.5	139.7	5.81	147.6	-0550	-0550
5.75	146.1	6.06	154	-0575	-0575
6	152.4	6.31	160.3	-0600	-0600
6.25	158.8	6.56	166.7	-0625	-0625
6.5	165.1	6.81	173	-0650	-0650
7	177.8	7.31	185.7	-0700	-0700
7.25	184.2	7.56	192.1	-0725	-0725
7.5	190.5	7.81	198.4	-0750	-0750



Standard Duty
Small Spring – B9226



Heavy Duty
Large Spring – B9224